SilverPower

SP-S750M
750W

Features:

- Super high efficiency for energy savings, up to 85% efficiency, 80 Plus Bronze approval.
- 3% line regulation for 3.3V/5V/+12V rail for maximum stability, security and performance.
- Dynamic Load on +12V to ensure maximum compatibility with mainboards and perhperials.
- High reliability Aluminum Electrolytic capacitors for increased product life and reliability.
- Active Power Factor Correctin [99% PF] for reduced line noise and power distortion.
- Advanced Dual Forward Converter circuit design for added reliability and efficiency.
- Smart and Silent Fan Control [S2FC], one of the best performance noise controller available on the market.
- 12cm double ball, ball bearing fan for increased airflow and lifetime and reduced noise levels.
- 12cm ball bearing fan mounted on soft rubber cushions to reduce fan vibration and rotation noises.
- Ultra ventilation [Honey Comb Structure] for increased airflow and reduced noise levels.
- 4x PCI-Express connectors to support high end graphics cards.
- All in One DC Cabling to support PC, IPC, workstations, servers and dual CPU systems.
- Patented Easy Swap peripheral connectors for easy plug and unplug connection.
- Total Protection with Over Voltage, Over Power and Short Circuit Protection.
- Universal AC Input for plug and run anywhere around the world.
- >100,000 hours MTBF, excluding fan.
- RoHS compliant.
- PFC Harmonics compliant, EN61000-3-2: 2000
- Safety approvals: TUV, Semko, CB & CE
- Meets Erp requirement
- Modular cable

MaxPoint Handelsgesellschaft mbH • Kurt-Fischer-Straße 50 • 22926 Ahrensburg • Germany • Tel.: +49-4102/468-800 • Fax: +49-4102/468-801
www.MaxPoint.de • info@MaxPoint.de • WEEE-Reg.-Nr.: DE88670488

SilverPower

Logistic Data	
Article number	13536
Article name	SP-S750M 750 W
EAN barcode	4250078133124
Mark (EAR registration number)	EAR888-62976468
Packing unit	4 pcs.
Net weight per piece	2.70 kg
Gross weight per piece	3.00 kg
Gross weight per carton	12.60 kg
Dimensions net (W x D x H)	159 x 150 x 86 mm
Dimensions gross (W x D x H)	192 x 300 x 133 mm
Dimensions gross per carton	550 x 220 x 330 mm
Accessory	1 x Power cord 4 x Chassis screws 1 x User manual 8 x Modular cables
Safety	TUV, Semko, CB & CE
Colour	Black
Customs tariff number	85044030
Land of Origin	PR China

Voltage table					
Model	**SP-S750M 750 Watt**				
AC Input	110-240V~ 10-5A 50-60Hz				
DC Output	+3.3 V	+5 V	+12 V	-12 V	+5 V_{SB}
Max. Amps	25 A	25 A	62 A	0.5 A	3 A
Max. comb. power	150 W		744 W	6 W	15 W
Total power	750 W				

Cable configuration		
Model	**Fixed cable**	**SP-S750M 750 Watt**
M/B (20 + 4P)	1	550 mm
ATX12V (4+4P)	1	550 mm
2 PCI-E (6+2P)	1	550 + 100 mm
	Modular cable	
EPS12V (8P)	1	550 mm
2 PCI-E (6+2P)	1	550 + 100 mm
3 SATA (5P)	2	550 + 150 + 150 mm
2 SATA (5P)	1	350 + 150 mm
3 Molex (4P)	1	550 + 150 + 150 mm
2 Molex (4P)	1	350 + 150 mm
2 FDD	1	140 mm

MaxPoint Handelsgesellschaft mbH • Kurt-Fischer-Straße 50 • 22926 Ahrensburg • Germany • Tel.: +49-4102/468-800 • Fax: +49-4102/468-801
www.MaxPoint.de • info@MaxPoint.de • WEEE-Reg.-Nr.: DE88670488